



WET TROLLEY

The range of the Linen Trolley includes both Dry Linen Trolley and Wet Linen Trolley to meet the various requirements of the clients with high quality of SS 304 Grade. Moreover, the Linen Trolleys are also available in comprehensive sizes and dimensions to meet the requisites of the application of keeping of clothes.



DRY TROLLEY

We have been consistently meeting the diverse and ever changing requirements of customers in the best possible manner by offering them a quality assured range of S.S Wet and Dry Linen Trolley at pocket friendly price with high quality of SS 304 Grade.

Size	Length	Width	Height
HLEPB	900MM	600MM	700MM

SAREE ROLLING MACHINE LPG GAS (LAUNDRY SPECIAL)

Saree Rolling Machine is preferably suited for ironing/rolling/ polishing different types of sarees. These machines are maintained with heavy duty springs for self-aligning. While ironing it eliminates any chance of damage. It runs with LPG gas with single phase current.

Model	Roller size (mm)	Useful Length (mm)	Motor (hp)	Spray	Dimension L×W×H (mm)	Net Weight KGS
HSRG	DIA 300	1600	1	×	2000 x 650 x 1300	275
HSRG	DIA 300	1600	1	✓	2000 x 940 x 1300	310
HSRG	DIA 400	1600	1	×	2000 x 650 x 1300	350
HSRG	DIA 400	1600	1	✓	2000 x 940 x 1300	380
HSRG	DIA 500	1600	1	×	2250 x 1080 x 1300	450
HSRG	DIA 500	1600	1	✓	2250 x 1375 x 1300	480
HSRG	DIA 600	1600	2	×	2250 x 1080 x 1300	550
HSRG	DIA 600	1600	2	✓	2250 x 1375 x 1300	580

SAREE ROLLING MACHINE ELECTRIC (LAUNDRY SPECIAL)

Saree Rolling Machine is preferably suited for ironing/rolling/ polishing different types of sarees. These machines are maintained with heavy duty springs for self-aligning. While ironing it eliminates any chance of damage. It requires 3 Phase current.

Model	Roller size (mm)	Useful Length (mm)	Motor (hp)	Heaters	KW	Spray	Dimension L×W×H (mm)	Net Weight KGS
HSRE	DIA 300	1600	1	3	9	×	2000 x 650 x 1300	275
HSRE	DIA 300	1600	1	3	9	✓	2000 x 940 x 1300	310
HSRE	DIA 400	1600	1	3	9	×	2000 x 650 x 1300	350
HSRE	DIA 400	1600	1	3	9	✓	2000 x 940 x 1300	380
HSRE	DIA 500	1600	1	3	18	×	2250 x 1080 x 1300	450
HSRE	DIA 500	1600	1	3	18	✓	2250 x 1375 x 1300	480
HSRE	DIA 600	1600	2	3	18	×	2250 x 1080 x 1300	550
HSRE	DIA 600	1600	2	3	18	✓	2250 x 1375 x 1300	580